

Foundations of Types in Isabelle/HOL

Simon Foster **Jim Woodcock**
University of York

18th August 2022

Overview

- 1 Relationship between sets and types
- 2 Defining new types using subsets
- 3 Description operators
- 4 Benefits and limitations of types



Outline

- 1 Relationship between sets and types
- 2 Defining new types using subsets
- 3 Description operators
- 4 Benefits and limitations of types

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$\text{UNIV} :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in \text{UNIV}$.
- All HOL types have at least one element, hence

$\exists x. x \in \text{UNIV} \quad \text{UNIV_witness}$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(\text{UNIV} :: \text{ocean set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}.$

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.
- All HOL types have at least one element, hence

$\exists x. x \in UNIV \quad UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}.$

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.
- All HOL types have at least one element, hence

$\exists x. x \in UNIV \quad UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}.$

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.

- All HOL types have at least one element, hence

$\exists x. x \in UNIV \quad UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}.$

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.
- All HOL types have at least one element, hence

$\exists x. x \in UNIV$ $UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}$.

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.
- All HOL types have at least one element, hence

$\exists x. x \in UNIV \quad UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}$.

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.
- All HOL types have at least one element, hence

$\exists x. x \in UNIV \quad UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic}, \text{Pacific}, \text{Indian}, \text{Arctic}\}.$

Types as Sets

- Every type T has corresponding non-empty set as its **universe**

$UNIV :: T \text{ set}$

- Any value $x :: T$ is an element of the type's universe $x \in UNIV$.
- All HOL types have at least one element, hence

$\exists x. x \in UNIV \quad UNIV_witness$

- Types are like **maximal sets**, the largest set of well-typed members.
- $(UNIV :: ocean \text{ set}) = \{\text{Atlantic, Pacific, Indian, Arctic}\}$.

Example: Equality Proofs

$$x \notin \mathcal{M}(\Gamma) \quad \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"

proof (rule equalityI; rule subsetI)

fix x :: ocean

assume "x ∈ UNIV"

show "x ∈ {Atlantic, Pacific, Indian, Arctic}"

by (cases x; simp) (* Automate Case Analysis *)

next

fix x :: ocean

assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"

show "x ∈ UNIV"

by (fact UNIV_I)

qed

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"

proof (rule equalityI; rule subsetI)

fix x :: ocean

assume "x ∈ UNIV"

show "x ∈ {Atlantic, Pacific, Indian, Arctic}"

by (cases x; simp) (* Automate Case Analysis *)

next

fix x :: ocean

assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"

show "x ∈ UNIV"

by (fact UNIV_I)

qed

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"

proof (rule equalityI; rule subsetI)

fix x :: ocean

assume "x ∈ UNIV"

show "x ∈ {Atlantic, Pacific, Indian, Arctic}"

by (cases x; simp) (* Automate Case Analysis *)

next

fix x :: ocean

assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"

show "x ∈ UNIV"

by (fact UNIV_I)

qed

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
```

```
proof (rule equalityI; rule subsetI)
```

```
  fix x :: ocean
```

```
  assume "x ∈ UNIV"
```

```
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
```

```
    by (cases x; simp) (* Automate Case Analysis *)
```

```
next
```

```
  fix x :: ocean
```

```
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
```

```
  show "x ∈ UNIV"
```

```
    by (fact UNIV_I)
```

```
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
```

```
proof (rule equalityI; rule subsetI)
```

```
  fix x :: ocean
```

```
  assume "x ∈ UNIV"
```

```
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
```

```
    by (cases x; simp) (* Automate Case Analysis *)
```

```
next
```

```
  fix x :: ocean
```

```
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
```

```
  show "x ∈ UNIV"
```

```
    by (fact UNIV_I)
```

```
qed
```

Example: Equality Proofs

$$x \notin \text{fv}(\Gamma) \frac{x \in A, \Gamma \vdash x \in B}{\Gamma \vdash A \subseteq B} \text{subsetI} \quad \frac{\Gamma \vdash A \subseteq B \quad \Gamma \vdash B \subseteq A}{\Gamma \vdash A = B} \text{equalityI}$$

```
lemma ocean_UNIV: "UNIV = {Atlantic, Pacific, Indian, Arctic}"
proof (rule equalityI; rule subsetI)
  fix x :: ocean
  assume "x ∈ UNIV"
  show "x ∈ {Atlantic, Pacific, Indian, Arctic}"
    by (cases x; simp) (* Automate Case Analysis *)
next
  fix x :: ocean
  assume "x ∈ {Atlantic, Pacific, Indian, Arctic}"
  show "x ∈ UNIV"
    by (fact UNIV_I)
qed
```

Outline

- 1 Relationship between sets and types
- 2 Defining new types using subsets
- 3 Description operators
- 4 Benefits and limitations of types

Types Definitions

- `type_synonym`, `datatype`, and `record` create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command `typedef`:

```
typedef NT = "A :: T set"by ...
```

- Requires a proof that the provided set A is **non-empty**.
- `typedef` is used internally by both `datatype` and `record`.
- Generates **conversion functions**:

```
Abs_NT :: T  $\Rightarrow$  NT
```

```
Rep_NT :: NT  $\Rightarrow$  T.
```

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

```
typedef NT = "A :: T set"by ...
```

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

```
Abs_NT :: T  $\Rightarrow$  NT
```

```
Rep_NT :: NT  $\Rightarrow$  T.
```

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

```
typedef NT = "A :: T set"by ...
```

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

```
Abs_NT :: T  $\Rightarrow$  NT
```

```
Rep_NT :: NT  $\Rightarrow$  T.
```

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

```
typedef NT = "A :: T set"by ...
```

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

```
Abs_NT :: T  $\Rightarrow$  NT
```

```
Rep_NT :: NT  $\Rightarrow$  T.
```

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

```
typedef NT = "A :: T set"by ...
```

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

```
Abs_NT :: T  $\Rightarrow$  NT
```

```
Rep_NT :: NT  $\Rightarrow$  T.
```

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

typedef NT = "A :: T set" **by** ...

- Requires a proof that the provided set *A* is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

Abs_NT :: T \Rightarrow NT

Rep_NT :: NT \Rightarrow T.

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

typedef NT = "A :: T set" **by** ...

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

$\text{Abs_NT} :: T \Rightarrow \text{NT}$

$\text{Rep_NT} :: \text{NT} \Rightarrow T.$

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

typedef NT = "A :: T set" **by** ...

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates conversion functions:

$\text{Abs_NT} :: T \Rightarrow \text{NT}$

$\text{Rep_NT} :: \text{NT} \Rightarrow T.$

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

typedef NT = "A :: T set" **by** ...

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

$\text{Abs_NT} :: T \Rightarrow \text{NT}$

$\text{Rep_NT} :: \text{NT} \Rightarrow T.$

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

typedef NT = "A :: T set" **by** ...

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

$Abs_NT :: T \Rightarrow NT$

$Rep_NT :: NT \Rightarrow T.$

Types Definitions

- **type_synonym**, **datatype**, and **record** create types.
- But there is a low-level mechanism.
- New types can be created from a **non-empty subset** of an existing type.
- Use the command **typedef**:

typedef NT = "A :: T set" **by** ...

- Requires a proof that the provided set A is **non-empty**.
- **typedef** is used internally by both **datatype** and **record**.
- Generates **conversion functions**:

$Abs_NT :: T \Rightarrow NT$

$Rep_NT :: NT \Rightarrow T.$

Types Definitions Visualised

```
typedef NT = "A :: T set" by ...
```

Types Definitions Visualised


```
typedef NT = "A :: T set" by ...
```

Types Definitions Visualised

```
typedef NT = "A :: T set" by ...
```

Original Type (T)

New Type (NT)



Conversion Functions

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.
- They satisfy:

$$\text{Abs_NT} (\text{Rep_NT } x) = x$$

$$x \in A \implies \text{Rep_NT} (\text{Abs_NT } x) = x$$

$$\text{Rep_NT } x \in A$$

Conversion Functions

```
typedef NT = "A :: T set" by ...
```

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.
- They satisfy:

$$\text{Abs_NT}(\text{Rep_NT } x) = x$$

$$x \in A \Rightarrow \text{Rep_NT}(\text{Abs_NT } x) = x$$

$$\text{Rep_NT } x \in A$$

Conversion Functions

```
typedef NT = "A :: T set" by ...
```

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.

- They satisfy:

$\text{Abs_NT}(\text{Rep_NT } x) = x$

$\text{Rep_NT}(\text{Abs_NT } x) = x$

$\text{Rep_NT } a \in A$

Conversion Functions

typedef NT = "A :: T set" **by** ...

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.
- They satisfy:

$$\text{Abs_NT} (\text{Rep_NT } x) = x$$

$$x \in A \implies \text{Rep_NT} (\text{Abs_NT } x) = x$$

$$\text{Rep_NT } x \in A$$

Conversion Functions

typedef NT = "A :: T set" **by** ...

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.
- They satisfy:

$$\text{Abs_NT} (\text{Rep_NT } x) = x$$

$$x \in A \implies \text{Rep_NT} (\text{Abs_NT } x) = x$$

$$\text{Rep_NT } x \in A$$

Conversion Functions

typedef NT = "A :: T set" **by** ...

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.
- They satisfy:

$$\text{Abs_NT} (\text{Rep_NT } x) = x$$

$$x \in A \implies \text{Rep_NT} (\text{Abs_NT } x) = x$$

$$\text{Rep_NT } x \in A$$

Conversion Functions

typedef NT = "A :: T set" **by** ...

- Conversion functions $\text{Abs_NT} :: T \Rightarrow \text{NT}$ and $\text{Rep_NT} :: \text{NT} \Rightarrow T$.
- They satisfy:

$$\text{Abs_NT} (\text{Rep_NT } x) = x$$

$$x \in A \implies \text{Rep_NT} (\text{Abs_NT } x) = x$$

$$\text{Rep_NT } x \in A$$

Example: Definining Non-Zero Numbers (1)

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ the does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
morphisms from_nat1 to_nat1  
by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
morphisms from_nat1 to_nat1  
by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- `typedef` creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero **nat** to a **nat**.
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat .
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that

$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (1)

Example

```
typedef nat1 = "{x :: nat. x > 0}"  
  morphisms from_nat1 to_nat1  
  by (rule_tac x="1" in exI, simp)
```

- Prove that $\{x :: \text{nat}. x > 0\}$ is non-empty by supplying witness 1.
- **typedef** creates $\text{from_nat1} :: \text{nat1} \Rightarrow \text{nat}$.
- That converts a non-zero nat to a nat .
- And $\text{to_nat1} :: \text{nat} \Rightarrow \text{nat1}$ it does the converse, such that
$$x > 0 \implies \text{from_nat1} (\text{to_nat1 } x) = x \quad (\text{to_nat1_inverse})$$

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.
- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.
- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.

```
definition plus1 :: "nat1  $\Rightarrow$  nat1  $\Rightarrow$  nat1" where  
  "plus1 x y = to_nat1 (from_nat1 x + from_nat1 y)"
```

- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.

```
definition plus1 :: "nat1  $\Rightarrow$  nat1  $\Rightarrow$  nat1" where  
  "plus1 x y = to_nat1 (from_nat1 x + from_nat1 y)"
```

```
lemma plus1:  
  assumes "x > 0" "y > 0"  
  shows "plus1 (to_nat1 x) (to_nat1 y) = to_nat1 (x+y)"  
  by (simp add: assms plus1_def to_nat1_inverse)
```

- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.

```
definition plus1 :: "nat1  $\Rightarrow$  nat1  $\Rightarrow$  nat1" where  
  "plus1 x y = to_nat1 (from_nat1 x + from_nat1 y)"
```

```
lemma plus1:  
  assumes "x > 0" "y > 0"  
  shows "plus1 (to_nat1 x) (to_nat1 y) = to_nat1 (x+y)"  
  by (simp add: assms plus1_def to_nat1_inverse)
```

- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.

```
definition plus1 :: "nat1  $\Rightarrow$  nat1  $\Rightarrow$  nat1" where  
  "plus1 x y = to_nat1 (from_nat1 x + from_nat1 y)"
```

```
lemma plus1:  
  assumes "x > 0" "y > 0"  
  shows "plus1 (to_nat1 x) (to_nat1 y) = to_nat1 (x+y)"  
  by (simp add: assms plus1_def to_nat1_inverse)
```

- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Example: Defining Non-Zero Numbers (2)

- We can define functions on `nat1` by **lifting** those on `nat`.

```
definition plus1 :: "nat1  $\Rightarrow$  nat1  $\Rightarrow$  nat1" where  
  "plus1 x y = to_nat1 (from_nat1 x + from_nat1 y)"
```

```
lemma plus1:  
  assumes "x > 0" "y > 0"  
  shows "plus1 (to_nat1 x) (to_nat1 y) = to_nat1 (x+y)"  
  by (simp add: assms plus1_def to_nat1_inverse)
```

- This process is automated with the **lifting package** (out of scope).
- But hold on, what is value of `to_nat1(0)`?
- This is underspecified, and so HOL assigns an **arbitrary value**.

Outline

- 1 Relationship between sets and types
- 2 Defining new types using subsets
- 3 Description operators**
- 4 Benefits and limitations of types

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.
- **Hilbert's choice**: pick a value $x :: T$ such that $P\ x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.
- Hilbert's choice: pick a value $x :: T$ such that $P\ x$ holds.
- Indefinite article in natural language: “a cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer general properties like $k \geq 0$ and $k \leq 3$.
- Relies on axiom of choice: can always pick a single element from a set.
- If no such x exists, return an arbitrary value of type T (e.g. $\epsilon x. False$).
- Uncomputable in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- Hilbert's choice: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “a cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer general properties like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as $SOME\ x :: T. P\ x$

- Hilbert's choice: pick a value $x :: T$ such that $P\ x$ holds.
- Indefinite article in natural language: “a cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer general properties like $k \geq 0$ and $k \leq 3$.
- Relies on axiom of choice: can always pick a single element from a set.
- If no such x exists, return an arbitrary value of type T (e.g. $\epsilon x. False$).
- Uncomputable in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “a cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
 - Relies on **axiom of choice**: can always pick a single element from a set.
 - If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
 - **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
 - Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as $SOME\ x :: T. P\ x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P\ x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Description Operators

- No accident that types are non-empty, but an **integral** part of the logic.

Indefinite Description Operator

$\epsilon x :: T. P x$ also written as *SOME* $x :: T. P x$

- **Hilbert's choice**: pick a value $x :: T$ such that $P x$ holds.
- Indefinite article in natural language: “**a** cat sitting on my roof”.
- $k \triangleq (\epsilon x. x \in \{0, 1, 2, 3\})$: could be 0, 1, 2, or 3.
- But we can infer **general properties** like $k \geq 0$ and $k \leq 3$.
- Relies on **axiom of choice**: can always pick a single element from a set.
- If no such x exists, return an **arbitrary** value of type T (e.g. $\epsilon x. False$).
- **Uncomputable** in general, e.g. what is $\epsilon x :: real. x * x = 2$?
- Lets us deal with partiality, e.g. $to_nat1(0)$, $x/0$, and $\sqrt{-1}$ (for \mathbb{R}).

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:
- We need to show some t exists satisfying P to reason about ϵ .
- **Very rarely** need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:
 - We need to show some t exists satisfying P to reason about ϵ .
 - *Very rarely* need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

- We need to show some t exists satisfying P to reason about ϵ .
- **Very rarely** need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin fv(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .
- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin fv(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .
- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin \text{fv}(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash \epsilon \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin \text{fv}(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash \epsilon \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin \text{fv}(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash \epsilon \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin \text{fv}(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash ? \in \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin \text{fv}(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash 0 \in \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin fv(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash 0 \in \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely need to reason about description operators directly.

Reasoning with Indefinite Descriptions

- Here's an introduction rule for indefinite description:

Introduction Rule

$$y \notin fv(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\epsilon x. P(x))} \text{someI2}$$

- We need to show some t exists satisfying P to reason about ϵ .

Example

$$\frac{\Gamma \vdash 0 \in \{0, 1, 2, 3\} \quad y \in \{0, 1, 2, 3\}, \Gamma \vdash y \leq 3}{\Gamma \vdash (\epsilon x. x \in \{0, 1, 2, 3\}) \leq 3}$$

- Very rarely** need to reason about description operators directly.

Example: Indefinite Descriptions

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"  
proof (rule some_equality)  
  show "(0::nat) < 1" by simp  
next  
  fix x :: nat  
  assume "x < 1"  
  thus "x = 0" by simp  
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
```

qed

Example: Indefinite Descriptions

Indefinite Description Equality Theorem (of someI)

$$x \notin \text{fv}(P, \Gamma) \frac{\Gamma \vdash P(a) \quad P(x), \Gamma \vdash x = a}{\Gamma \vdash (\epsilon x. P x) = a} \text{some_equality}$$

Example

```
lemma nat_less1_0: "(SOME x :: nat. x < 1) = 0"
proof (rule some_equality)
  show "(0::nat) < 1" by simp
next
  fix x :: nat
  assume "x < 1"
  thus "x = 0" by simp
qed
```

Definite Descriptions

- Gives the unique value x described by P .
- Like definite article in natural language: “the cat sitting on my roof”.
- Meaningful only when there is precisely one x satisfying P .

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as *THE* $x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “the cat sitting on my roof”.
- Meaningful only when there is precisely one x satisfying P .

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as *THE* $x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “the cat sitting on my roof”.
- Meaningful only when there is precisely one x satisfying P .

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as $THE x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “the cat sitting on my roof”.
- Meaningful only when there is precisely one x satisfying P .

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as $THE x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “**the** cat sitting on my roof”.
- Meaningful only when there is precisely one x satisfying P .

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as $THE x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “**the** cat sitting on my roof”.
- Meaningful only when there is **precisely one** x satisfying P .

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as $THE x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “**the** cat sitting on my roof”.
- Meaningful only when there is **precisely one** x satisfying P .

Introduction Rule

Definite Descriptions

Definite Description Operator

$\iota x :: T. P x$ also written as $THE x :: T. P x$

- Gives the unique value x described by P .
- Like definite article in natural language: “**the** cat sitting on my roof”.
- Meaningful only when there is **precisely one** x satisfying P .

Introduction Rule

$$y \notin fv(\Gamma, P, Q) \frac{\Gamma \vdash P(t) \quad P(y), \Gamma \vdash y = t \quad P(y), \Gamma \vdash Q(y)}{\Gamma \vdash Q(\iota x. P(x))} \text{theI2}$$

Outline

- 1 Relationship between sets and types
- 2 Defining new types using subsets
- 3 Description operators
- 4 Benefits and limitations of types**

Types vs. Sets

Types and sets seem quite similar. Why have both?

In set vs. P.A., 'a' vs. 'b' vs. $A \times B$ vs. $B \times A$.

Types resolve problems in naive set theory.

Russell's paradox:

Let $R = \{x \mid x \notin x\}$ then $R \in R \leftrightarrow R \notin R$ is consistent!

Types vs. Sets

- Types and sets seem quite similar. Why have both?

'a set vs. $\mathbb{P} A$, 'a \times 'b vs. $A \times B$ etc.

- Types resolve problems in naive set theory.

- Russell's paradox:

Let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$ inconsistent!

Types vs. Sets

- Types and sets seem quite similar. Why have both?

'a set vs. $\mathbb{P} A$, 'a \times 'b vs. $A \times B$ etc.

- Types resolve problems in naive set theory.

- Russell's paradox:

Let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$ inconsistent!

Types vs. Sets

- Types and sets seem quite similar. Why have both?

'a set vs. $\mathbb{P} A$, 'a \times 'b vs. $A \times B$ etc.

- Types resolve problems in naive set theory.

- Russell's paradox:

Let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$ inconsistent!

Types vs. Sets

- Types and sets seem quite similar. Why have both?

'a set vs. $\mathbb{P} A$, 'a \times 'b vs. $A \times B$ etc.

- Types resolve problems in naive set theory.

- Russell's paradox:

Let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$ inconsistent!

Types vs. Sets

- Types and sets seem quite similar. Why have both?

'a set vs. $\mathbb{P} A$, 'a \times 'b vs. $A \times B$ etc.

- Types resolve problems in naive set theory.

- Russell's paradox:

Let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$ inconsistent!.

Russell's Paradox (Proof Attempt)

⚡

$\Gamma \vdash R \in R$
not_not
 $\Gamma \vdash \neg(R \notin R)$
mem_Collect_eq
 $\Gamma \vdash R \notin \{x \mid x \notin x\}$
R_def
 $\Gamma \vdash R \notin R$
 β -reduction
 $\Gamma \vdash (\lambda x. x \notin x) R$
mem_Collect_eq
 $\Gamma \vdash R \in \{x \mid x \notin x\}$
R_def
 $\Gamma \vdash R \in R$

Russell's Paradox (Proof Attempt)

⚡

$\Gamma \vdash R \in R$
not_not
 $\Gamma \vdash \neg(R \notin R)$
mem_Collect_eq
 $\Gamma \vdash R \notin \{x \mid x \notin x\}$
R_def
 $\Gamma \vdash R \notin R$
 β -reduction
 $\Gamma \vdash (\lambda x. x \notin x) R$
mem_Collect_eq
 $\Gamma \vdash R \in \{x \mid x \notin x\}$
R_def
 $\Gamma \vdash R \in R$

Russell's Paradox (Proof Attempt)

⚡

$$\frac{\begin{array}{c} \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \text{R_def} \\ \Gamma \vdash R \notin R \\ \beta\text{-reduction} \\ \Gamma \vdash (\lambda x. x \notin x) R \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \in \{x \mid x \notin x\} \end{array}}{\Gamma \vdash R \in R} \text{R_def}$$

Russell's Paradox (Proof Attempt)

⚡

$$\frac{\begin{array}{c} \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \text{R_def} \\ \Gamma \vdash R \notin R \\ \beta\text{-reduction} \\ \Gamma \vdash (\lambda x. x \notin x) R \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \in \{x \mid x \notin x\} \end{array}}{\Gamma \vdash R \in R} \text{R_def}$$

Russell's Paradox (Proof Attempt)

⚡

$$\begin{array}{c} \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \text{R_def} \\ \Gamma \vdash R \notin R \\ \beta\text{-reduction} \\ \Gamma \vdash (\lambda x. x \notin x) R \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

⚡

$$\begin{array}{c} \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \text{R_def} \\ \Gamma \vdash R \notin R \\ \beta\text{-reduction} \\ \Gamma \vdash (\lambda x. x \notin x) R \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

⚡

$$\begin{array}{c} \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \text{R_def} \\ \Gamma \vdash R \notin R \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

⚡

$$\begin{array}{c} \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \text{R_def} \\ \hline \Gamma \vdash R \notin R \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

$$\begin{array}{c} \text{⚡} \\ \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \hline \Gamma \vdash R \notin R \quad \text{R_def} \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

$$\begin{array}{c} \text{⚡} \\ \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \hline \Gamma \vdash R \notin R \quad \text{R_def} \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

$$\begin{array}{c} \text{⚡} \\ \Gamma \vdash R \in R \\ \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \hline \Gamma \vdash R \notin \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \notin R \quad \text{R_def} \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

⚡

$\Gamma \vdash R \in R$
not_not

$\Gamma \vdash \neg(R \notin R)$

$\frac{\Gamma \vdash \neg(R \notin R)}{\Gamma \vdash R \notin \{x \mid x \notin x\}}$ mem_Collect_eq

$\frac{\Gamma \vdash R \notin \{x \mid x \notin x\}}{\Gamma \vdash R \notin R}$ R_def

$\frac{\Gamma \vdash R \notin R}{\Gamma \vdash (\lambda x. x \notin x) R}$ β -reduction

$\frac{\Gamma \vdash (\lambda x. x \notin x) R}{\Gamma \vdash R \in \{x \mid x \notin x\}}$ mem_Collect_eq

$\frac{\Gamma \vdash R \in \{x \mid x \notin x\}}{\Gamma \vdash R \in R}$ R_def

$\Gamma \vdash R \in R$

Russell's Paradox (Proof Attempt)

$$\begin{array}{c} \text{⚡} \\ \hline \Gamma \vdash R \in R \\ \hline \text{not_not} \\ \Gamma \vdash \neg(R \notin R) \\ \hline \text{mem_Collect_eq} \\ \Gamma \vdash R \notin \{x \mid x \notin x\} \\ \hline \text{R_def} \\ \Gamma \vdash R \notin R \\ \hline \beta\text{-reduction} \\ \Gamma \vdash (\lambda x. x \notin x) R \\ \hline \text{mem_Collect_eq} \\ \Gamma \vdash R \in \{x \mid x \notin x\} \\ \hline \text{R_def} \\ \Gamma \vdash R \in R \end{array}$$

Russell's Paradox (Proof Attempt)



$$\begin{array}{c} \frac{\Gamma \vdash R \in R}{\Gamma \vdash \neg(R \notin R)} \text{not_not} \\ \frac{\Gamma \vdash \neg(R \notin R)}{\Gamma \vdash R \notin \{x \mid x \notin x\}} \text{mem_Collect_eq} \\ \frac{\Gamma \vdash R \notin \{x \mid x \notin x\}}{\Gamma \vdash R \notin R} \text{R_def} \\ \frac{\Gamma \vdash R \notin R}{\Gamma \vdash (\lambda x. x \notin x) R} \beta\text{-reduction} \\ \frac{\Gamma \vdash (\lambda x. x \notin x) R}{\Gamma \vdash R \in \{x \mid x \notin x\}} \text{mem_Collect_eq} \\ \frac{\Gamma \vdash R \in \{x \mid x \notin x\}}{\Gamma \vdash R \in R} \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

$$\begin{array}{c} \text{⚡} \\ \hline \Gamma \vdash R \in R \\ \hline \Gamma \vdash \neg(R \notin R) \quad \text{not_not} \\ \hline \Gamma \vdash R \notin \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \notin R \quad \text{R_def} \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Russell's Paradox (Proof Attempt)

$$\begin{array}{c} \text{⚡} \\ \hline \Gamma \vdash R \in R \\ \hline \Gamma \vdash \neg(R \notin R) \quad \text{not_not} \\ \hline \Gamma \vdash R \notin \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \notin R \quad \text{R_def} \\ \hline \Gamma \vdash (\lambda x. x \notin x) R \quad \beta\text{-reduction} \\ \hline \Gamma \vdash R \in \{x \mid x \notin x\} \quad \text{mem_Collect_eq} \\ \hline \Gamma \vdash R \in R \quad \text{R_def} \end{array}$$

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naive set theory.
 - Russell's paradox: let $R = \{x \mid x \notin x\}$ then $R \in R$ or $R \notin R$.
 - Excluded by HQT, since $x \in x$ and $x \notin x$ are both ill-typed.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$.
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- Conclusion: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- Russell's paradox: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both ill-typed.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- Conclusion: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- Russell's paradox: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both ill-typed.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- Conclusion: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Types vs. Sets

- Types and sets seem quite similar – why have both?
- Types resolve problems in naïve set theory.
- **Russell's paradox**: let $R = \{x \mid x \notin x\}$ then $R \in R \Leftrightarrow R \notin R$.
- Excluded by HOL since $x \in x$ and $x \notin x$ are both **ill-typed**.
- Sets are more flexible, e.g. we can have $A \cup B$ and $A \subseteq B$
- But no equivalents for types.
- Type checking $x :: T$ is decidable, but $x \in A$ requires proof.
- In general, types improve automation by enforcing specific patterns.
- **Conclusion**: We need both. It takes experience to know which to use.

Conclusion

Next Lecture

→ Automation and slogdturner

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

- Automation and sledgehammer.

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

● Automation and sledgehammer.

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

● Automation and sledgehammer.

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

● Automation and Sledgehammer

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

De Automation and Design

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

- Automation and sledghammer.

Conclusion

This Lecture

- Relationship between sets and types.
- Defining new types using subsets.
- Description operators.
- Benefits and limitations of types.

Next Lecture

- Automation and sledghammer.